

biblio.webquery api

API Documentation

May 6, 2009

Contents

Contents	1
1 Package biblio.webquery	2
1.1 Modules	2
2 Module biblio.webquery.basewebquery	3
2.1 Class BaseWebquery	3
2.1.1 Methods	3
2.1.2 Properties	4
2.2 Class BaseKeyedWebQuery	4
2.2.1 Methods	5
2.2.2 Properties	5
3 Module biblio.webquery.bibrecord	6
3.1 Variables	6
3.2 Class BibRecord	6
3.2.1 Methods	6
3.2.2 Properties	7
3.3 Class PersonalName	7
3.3.1 Methods	8
3.3.2 Properties	8
4 Module biblio.webquery.errors	9
4.1 Class QueryError	9
4.1.1 Methods	9
4.1.2 Properties	9
4.2 Class ParseError	10
4.2.1 Methods	10
4.2.2 Properties	11
4.3 Class QueryThrottleError	11
4.3.1 Methods	11
4.3.2 Properties	12
5 Module biblio.webquery.impl	13
5.1 Functions	13
5.2 Class ReprObj	13
5.2.1 Methods	13
5.2.2 Properties	14

6	Module biblio.webquery.isbndb	15
6.1	Functions	15
6.2	Class IsbndbQuery	15
6.2.1	Methods	15
6.2.2	Properties	17
7	Module biblio.webquery.loc	18
7.1	Variables	18
7.2	Class LocQuery	18
7.2.1	Methods	18
7.2.2	Properties	19
8	Module biblio.webquery.querythrottle	20
8.1	Variables	20
8.2	Class BaseQueryThrottle	20
8.2.1	Methods	20
8.2.2	Properties	21
8.3	Class WaitNSecondsThrottle	22
8.3.1	Methods	22
8.3.2	Properties	23
8.4	Class WaitOneSecondThrottle	23
8.4.1	Methods	24
8.4.2	Properties	24
8.5	Class AbsoluteNumberThrottle	24
8.5.1	Methods	25
8.5.2	Properties	26
8.6	Class Max500Throttle	26
8.6.1	Methods	26
8.6.2	Properties	26
9	Package biblio.webquery.scripts	27
9.1	Modules	27
10	Module biblio.webquery.scripts.common	28
10.1	Functions	28
10.2	Variables	28
11	Module biblio.webquery.scripts.config	29
11.1	Variables	29
12	Module biblio.webquery.scripts.queryisbn	30
12.1	Functions	30
12.2	Variables	30
13	Module biblio.webquery.scripts.renamebyisbn	31
13.1	Functions	31
13.2	Variables	31
14	Module biblio.webquery.utils	33
14.1	Functions	33
14.2	Variables	36
15	Module biblio.webquery.worldcat	37
15.1	Functions	37

15.2 Variables	38
15.3 Class WorldcatQuery	38
15.3.1 Methods	39
15.3.2 Properties	39
16 Module biblio.webquery.xisbn	40
16.1 Functions	40
16.2 Class XisbnQuery	40
16.2.1 Methods	40
16.2.2 Properties	42
17 Module xml.etree.ElementTree	43
17.1 Functions	43
17.2 Variables	43
17.3 Class ElementTree	43
17.3.1 Methods	43
17.4 Class QName	44
17.4.1 Methods	44
17.5 Class TreeBuilder	44
17.5.1 Methods	44
17.6 Class XMLTreeBuilder	45
17.6.1 Methods	45
17.7 Class XMLTreeBuilder	45
17.7.1 Methods	45
17.8 Class iterparse	45
17.8.1 Methods	45

1 Package *biblio.webquery*

Querying webservices for bibliographic information. **Version:** 0.4b

1.1 Modules

- **basewebquery**: A base class for querying webservices.
(Section 2, p. 3)
- **bibrecord**: Classes for representing bibliographic records and authors.
(Section 3, p. 6)
- **errors**: Various errors thrown by the the module.
(Section 4, p. 9)
- **impl**: Various (fragile) implementation details and utilities.
(Section 5, p. 13)
- **isbndb**: Querying the ISBNDb for bibliographic information.
(Section 6, p. 15)
- **loc**: Querying the Library of Congress for bibliographic information.
(Section 7, p. 18)
- **querythrottle**: Classes for throttling web-queries, so as to stay within limits.
(Section 8, p. 20)
- **scripts**: Scripts that use *biblio.webquery*.
(Section 9, p. 27)
 - **common**: Function shared between the scripts.
(Section 10, p. 28)
 - **config**: Constants and definitions for scripts.
(Section 11, p. 29)
 - **queryisbn**: Retrieve bibliographic information for a given ISBN.
(Section 12, p. 30)
 - **renamebyisbn**: Rename files as by the ISBN buried in their original name.
(Section 13, p. 31)
- **utils**: Various utilities.
(Section 14, p. 33)
- **worldcat**: Querying WorldCat for bibliographic information and normalising the results.
(Section 15, p. 37)
- **xisbn**: Querying WorldCat xISBN service for bibliographic information.
(Section 16, p. 40)

2 Module *biblio.webquery.basewebquery*

A base class for querying webservices.

2.1 Class *BaseWebquery*



Known Subclasses: *biblio.webquery.basewebquery.BaseKeyedWebQuery*, *biblio.webquery.xisbn.XisbnQuery*, *biblio.webquery.worldcat.WorldcatQuery*, *biblio.webquery.loc.LocQuery*

A base class for querying webservices.

This serves as a foundation for other web-query classes, centralising a small amount of functionality and providing a common interface.

2.1.1 Methods

`__init__(self, root_url, timeout=5.0, limits=[])`

Ctor, allowing the setting of the webservice, timeout and limits on use. **Parameters**

root_url: The url to be used as the basis for all requests to this service. It should be the common “stem” that does not vary for any request.
(*type=string*)

timeout: How many seconds to wait for a response. (*type=int or float*)

limits: A list of *QueryThrottles* to impose upon the use of this webservice.
(*type=iterable*)

Overrides: *object.__init__*

`request(self, sub_url)`

Send a request to the webservice and return the response.

This is the low-level calls that checks any throttling, send the request and actually fetches the response data. For consistency, all service access should be placed through here.

Parameters

sub_url: This will be added to the root url set in the c’tor and used as the actual url that is requested. (*type=string*)

Return Value

The data in the webservice response.

*Inherited from *biblio.webquery.impl.ReprObj*(Section 5.2)*

`__repr__()`, `__str__()`, `__unicode__()`


Inherited from object

`__delattr__()`, `__getattr__()`, `__hash__()`, `__new__()`, `__reduce__()`, `__reduce_ex__()`, `__setattr__()`

2.1.2 Properties

Name	Description
<i>Inherited from object</i>	
<code>__class__</code>	

2.2 Class BaseKeyedWebQuery



Known Subclasses: `biblio.webquery.isbndb.IsbndbQuery`

A Webquery that requires an access key.

2.2.1 Methods

<code>__init__(self, root_url, key, timeout=5.0, limits=[])</code>
<p>Ctor, allowing the setting of a webservice access key. Parameters</p> <p>root_url: See BaseWebquery. Either this or the sub_url passed to request must include a keyword formatting for the access key, i.e. <code>%(key)s</code>.</p> <p>key: The access or PAI key to be passed to the webservice for access. (<i>type=string</i>)</p> <p>timeout: See BaseWebquery.</p> <p>limits: See BaseWebquery.</p> <p>Overrides: <code>object.__init__</code></p>

Inherited from `biblio.webquery.basewebquery.BaseWebquery` (Section 2.1)

`request()`

Inherited from `biblio.webquery.impl.ReprObj` (Section 5.2)

`__repr__()`, `__str__()`, `__unicode__()`

Inherited from `object`

`__delattr__()`, `__getattribute__()`, `__hash__()`, `__new__()`, `__reduce__()`, `__reduce_ex__()`, `__setattr__()`

2.2.2 Properties

Name	Description
<i>Inherited from <code>object</code></i>	
<code>__class__</code>	

3 Module biblio.webquery.bibrecord

Classes for representing bibliographic records and authors.

These are not the intended major function of this module, but are necessary for translation between formats.

Variously based upon:

- pymarc
- bibconverter
- bibliograph.core and bibliograph.parsing

3.1 Variables

Name	Description
SHORT_TITLE_SPLIT_RE	Value: <code>re.compile(r'[:\?]')</code>

3.2 Class BibRecord



3.2.1 Methods

<code>__init__(self)</code>
C'tor. Overrides: <code>object.__init__</code>
<code>add_ext_references(self, key, val)</code>
<code>get_short_title(self)</code>

Inherited from `biblio.webquery.impl.ReprObj` (Section 5.2)

`__repr__()`, `__str__()`, `__unicode__()`

Inherited from object

`__delattr__()`, `__getattr__()`, `__hash__()`, `__new__()`, `__reduce__()`, `__reduce_ex__()`,
`__setattr__()`

3.2.2 Properties

Name	Description
<code>short_title</code>	
<i>Inherited from object</i>	
<code>__class__</code>	

3.3 Class *PersonalName*



A name, as used for authors and editors.

The terms 'given', 'other' and 'family' are used in preference to other schemes, as they are more culture-neutral and do not assume any particular ordering.

given The first / christian or forename, e.g. 'John'.

other Any middle names, e.g. 'James Richard'.

family surname, last name, e.g. 'Smith'.

3.3.1 Methods

<code>__init__(self, given, other=None, family=None, title=None, prefix=None, suffix=None)</code>

C'tor, requiring only the given name.

Note that the only required argument is the given name, allowing single names (e.g. 'Madonna'). Also the order of positional arguments allows a regular name to be passed as 'John', 'James', 'Smith'. Overrides: `object.__init__`

<code>__unicode__(self)</code>

Return a readable formatted version of the name. Overrides: `biblio.webquery.impl.ReprObj.__unicode__`

<code>__repr__(self)</code>

Return a representation of this object. Overrides: `object.__repr__`

Inherited from `biblio.webquery.impl.ReprObj` (Section 5.2)

`__str__()`

Inherited from `object`

`__delattr__()`, `__getattr__()`, `__hash__()`, `__new__()`, `__reduce__()`, `__reduce_ex__()`, `__setattr__()`


3.3.2 Properties

Name	Description
<i>Inherited from <code>object</code></i>	
<code>__class__</code>	

4 Module `biblio.webquery.errors`

Various errors thrown by the the module.

4.1 Class `QueryError`



Raised when there is an problem with a queries reply.

4.1.1 Methods

<code>__init__(self, msg)</code>
C'tor. Overrides: <code>object.__init__</code>

Inherited from `exceptions.ValueError`

`__new__()`

Inherited from `exceptions.BaseException`

`__delattr__()`, `__getattr__()`, `__getitem__()`, `__getslice__()`, `__reduce__()`, `__repr__()`,
`__setattr__()`, `__setstate__()`, `__str__()`


Inherited from `object`

`__hash__()`, `__reduce_ex__()`

4.1.2 Properties

Name	Description
<i>Inherited from <code>exceptions.BaseException</code></i>	
<code>args</code> , <code>message</code>	
<i>Inherited from <code>object</code></i>	
<code>__class__</code>	

4.2 Class `ParseError`



Thrown when parsing webservice formats.

4.2.1 Methods

<code>__init__(self, msg)</code>
C'tor. Overrides: <code>object.__init__</code>

Inherited from `exceptions.ValueError`

`__new__()`

Inherited from `exceptions.BaseException`

`__delattr__()`, `__getattr__()`, `__getitem__()`, `__getslice__()`, `__reduce__()`, `__repr__()`,
`__setattr__()`, `__setstate__()`, `__str__()`


Inherited from `object`

`__hash__()`, `__reduce_ex__()`

4.2.2 Properties

Name	Description
<i>Inherited from <code>exceptions.BaseException</code></i>	
<code>args</code> , <code>message</code>	
<i>Inherited from <code>object</code></i>	
<code>__class__</code>	

4.3 Class `QueryThrottleError`



An exception to throw when a query limit has been exceeded.

It serves little purpose except to distinguish failures caused by exceeding query limits.

4.3.1 Methods

<code>__init__(self, msg=None)</code> <code>x.__init__(...)</code> initializes <code>x</code> ; see <code>x.__class__.__doc__</code> for signature Overrides: <code>object.__init__</code> <code>exitit</code> (inherited documentation)

Inherited from `exceptions.RuntimeError`

`__new__()`

Inherited from `exceptions.BaseException`

`__delattr__()`, `__getattr__()`, `__getitem__()`, `__getslice__()`, `__reduce__()`, `__repr__()`,
`__setattr__()`, `__setstate__()`, `__str__()`

Inherited from `object`

`__hash__()`, `__reduce_ex__()`

4.3.2 Properties

Name	Description
	<i>Inherited from exceptions.BaseException</i>
	args, message
	<i>Inherited from object</i>
<code>__class__</code>	

5 Module *biblio.webquery.impl*

Various (fragile) implementation details and utilities.

Don't reply on these because they may go away.

5.1 Functions

```
assert_or_raise(cond, error_cls, error_msg=None)
```

If a condition is not met, raise a assertion with this message.

5.2 Class *ReprObj*

```
object └─
        biblio.webquery.impl.ReprObj
```

Known Subclasses: *biblio.webquery.querythrottle.BaseQueryThrottle*, *biblio.webquery.basewebquery.B*
biblio.webquery.bibrecord.BibRecord, *biblio.webquery.bibrecord.PersonalName*

A class with an simple and consistent printable version.

5.2.1 Methods

```
__str__(self)
```

```
str(x)
```

Overrides: *object.__str__* extit(inherited documentation)

```
__unicode__(self)
```

```
__repr__(self)
```

```
repr(x)
```

Overrides: *object.__repr__* extit(inherited documentation)

Inherited from object

```
__delattr__(), __getattr__(), __hash__(), __init__(), __new__(), __reduce__(),  

__reduce_ex__(), __setattr__()
```

5.2.2 Properties

Name	Description
<i>Inherited from object</i>	
__class__	

6 Module *biblio.webquery.isbndb*

Querying the ISBNDb for bibliographic information.

6.1 Functions

<code>isbndb_xml_to_bibrecords(<i>xml_txt</i>)</code>

6.2 Class *IsbndbQuery*

object └

biblio.webquery.impl.ReprObj └

biblio.webquery.basewebquery.BaseWebquery └

biblio.webquery.basewebquery.BaseKeyedWebQuery └ *biblio.webquery.isbndb.IsbndbQuery*

6.2.1 Methods

<code>__init__(<i>self</i>, <i>key</i>, <i>timeout</i>=5.0, <i>limits</i>=None)</code>
--

C'tor, accepting an access key. **Parameters**

root_url: See *BaseWebquery*. Either this or the *sub_url* passed to **request** must include a keyword formatting for the access key, i.e. *%(key)s*.

key: The access or PAI key to be passed to the webservice for access.

timeout: See *BaseWebquery*.

limits: See *BaseWebquery*.

Overrides: *object.__init__*

query_service(*self, index, value, results*)

A generalised query for ISBNdb.

This serves a general way of accessing all the methods available for ISBNdb. It also normalises the ISBN to a suitable form for submission. Note that it is probably possible to form a bad query with the wrong combination of parameters. **Parameters**

index: The index to search in ISBNdb. (*type=string*)
value: The value to search for in the index.. (*type=string*)
results: A list of the data to include in the response.
(*type=iterable*)

Return Value

The response received from the service.

query_bibdata_by_isbn(*self, isbn, format='bibrecord'*)

Return publication data based on ISBN. **Parameters**

isbn: An ISBN-10 or ISBN-13. (*type=string*)
format: The desired format for the results. (*type=string*)

Return Value

Publication data in Xisbn XML format.

query_author_by_name(*self, name, fields=None*)

Search author data based on name. **Parameters**

name: The name to search for. (*type=string*)
fields: What result blocks to return.. (*type=iterable*)

Return Value

Publication data in ISBNdb XML format.

query_author_by_id (<i>self</i> , <i>auth_id</i> , <i>fields</i> =None)

Search author data based on ID. **Parameters**

auth_id: The ISBN “person_id” to search for. (*type=string*)

fields: What result blocks to return.. (*type=iterable*)

Return Value

Publication data in ISBNdb XML format.

Inherited from biblio.webquery.basewebquery.BaseWebquery(Section 2.1)

request()

Inherited from biblio.webquery.impl.ReprObj(Section 5.2)

__repr__(), __str__(), __unicode__()

Inherited from object

__delattr__(), __getattr__(), __hash__(), __new__(), __reduce__(), __reduce_ex__(),
__setattr__()

6.2.2 Properties

Name	Description
<i>Inherited from object</i>	
__class__	

7 Module *biblio.webquery.loc*

Querying the Library of Congress for bibliographic information.

7.1 Variables

Name	Description
LOC_ROOTURL	Value: 'http://z3950.loc.gov:7090/voyager?operation=searchRetrie...

7.2 Class *LocQuery*

object └

biblio.webquery.impl.ReprObj └

biblio.webquery.basewebquery.BaseWebquery └
biblio.webquery.loc.LocQuery

7.2.1 Methods

<code>__init__(self, timeout=5.0, limits=None)</code>
<p>C'tor. Parameters</p> <p>root_url: The url to be used as the basis for all requests to this service. It should be the common “stem” that does not vary for any request.</p> <p>timeout: How many seconds to wait for a response.</p> <p>limits: A list of QueryThrottles to impose upon the use of this webservice.</p> <p>Overrides: object.__init__</p>
<code>query_bibdata_by_isbn(self, isbn, format='MODS')</code>
<p>Return the metadata for a publication specified by ISBN.</p>

Inherited from biblio.webquery.basewebquery.BaseWebquery(Section 2.1)

request()

Inherited from biblio.webquery.impl.ReprObj(Section 5.2)

__repr__(), __str__(), __unicode__()

Inherited from object

__delattr__(), __getattr__(), __hash__(), __new__(), __reduce__(), __reduce_ex__(),
__setattr__()

7.2.2 Properties

Name	Description
<i>Inherited from object</i>	
__class__	

8 Module `biblio.webquery.querythrottle`

Classes for throttling web-queries, so as to stay within limits.

8.1 Variables

Name	Description
<code>FAIL_AND_RAISE</code>	Value: <code>'RAISE'</code>
<code>FAIL_AND_WAIT</code>	Value: <code>'WAIT'</code>

8.2 Class `BaseQueryThrottle`



Known Subclasses: `biblio.webquery.querythrottle.AbsoluteNumberThrottle`, `biblio.webquery.querythrottle`

A limit upon query usage.

Often webservises will request that users restrict themselves to a request every second, or no more than 1000 a day, etc. This is a base class for implementing those limits. Different restrictions can be implemented in derived classes.

Limits are constructed with set behaviour

8.2.1 Methods

<code>__init__(self, fail_action=None, wait_duration=1.0)</code>
Ctor, allowing the polling period and failure behaviour to be set. Overrides: <code>object.__init__</code>

check_limit(*self*, *wquery*)

Has the query exceeded its limit?

This is a primarily internal method for testing whether a limit has been reached. Handling that circumstance is left to the calling method **check_limit**. This should be overridden in derived class to implement different throttling methods. **Parameters**

wquery: The object or service to be throttled. This allows the same limit to service several objects in different ways (e.g. by having them share the same limit, or be handled independently).

Return Value

A boolean, giving whether the query is within limit or not.

within_limit(*self*, *wquery*)

Has the query exceeded its limit?

This should be called by services to test whether a limit has been reached. Handling that circumstance is left to the calling method **check_limit**. This should be overridden in derived class to implement different throttling methods. **Parameters**

wquery: See **check_limit**

log_success(*self*, *wquery*)

Successful queries will probably effect the success of future ones, so here is a place to log them.

*Inherited from **biblio.webquery.impl.ReprObj**(Section 5.2)*

`__repr__()`, `__str__()`, `__unicode__()`


*Inherited from **object***

`__delattr__()`, `__getattr__()`, `__hash__()`, `__new__()`, `__reduce__()`, `__reduce_ex__()`, `__setattr__()`

8.2.2 Properties

Name	Description
<i>Inherited from object</i>	
<code>__class__</code>	

8.3 Class `WaitNSecondsThrottle`



Known Subclasses: `biblio.webquery.querythrottle.WaitOneSecondThrottle`

Limit a query to every N seconds at most.

By default this throttle holds the query until the wait period is over. Note that this throttle can be used across a set of queries, so that the limit applies for the set. In this case the waiting behaviour could be undesirable, with a large population of queries on hold.

8.3.1 Methods

<code>__init__</code> (<i>self</i> , <i>wait</i> , <i>fail_action</i> = <code>'WAIT'</code>)
C'tor, allowing the wait period and failure behaviour to be set. Parameters <i>wait</i> : The period to enforce between queries. (<i>type</i> = <i>int</i> or <i>float</i>) <i>fail_action</i> : See <code>BaseQueryThrottle</code> . Overrides: <code>object.__init__</code>
<code>within_limit</code> (<i>self</i> , <i>wquery</i>)
Has it been longer than the wait period since the last query? Parameters <i>wquery</i> : See <code>check_limit</code> Overrides: <code>biblio.webquery.querythrottle.BaseQueryThrottle.within_limit</code>

`log_success(self, wquery)`

Sucessful queries will probably effect the success of future ones, so here is a place to log them. Overrides:
`biblio.webquery.querythrottle.BaseQueryThrottle.log_success` extit(inherited documentation)

Inherited from `biblio.webquery.querythrottle.BaseQueryThrottle`(Section 8.2)

`check_limit()`

Inherited from `biblio.webquery.impl.ReprObj`(Section 5.2)

`__repr__()`, `__str__()`, `__unicode__()`


Inherited from object

`__delattr__()`, `__getattr__()`, `__hash__()`, `__new__()`, `__reduce__()`, `__reduce_ex__()`, `__setattr__()`

8.3.2 Properties

Name	Description
<i>Inherited from object</i>	
<code>__class__</code>	

8.4 Class `WaitOneSecondThrottle`



Limit a query to once every second at most.
This is a common limit, and so is provided as a convenience.

8.4.1 Methods

`__init__(self, fail_action='WAIT')`
 C'tor, allowing the wait period and failure behaviour to be set. **Parameters**
 wait: The period to enforce between queries.
 fail_action: See `BaseQueryThrottle`.
 Overrides: `object.__init__` `exitit`(inherited documentation)

Inherited from `biblio.webquery.querythrottle.WaitNSecondsThrottle` (Section 8.3)

`log_success()`, `within_limit()`

Inherited from `biblio.webquery.querythrottle.BaseQueryThrottle` (Section 8.2)

`check_limit()`

Inherited from `biblio.webquery.impl.ReprObj` (Section 5.2)

`__repr__()`, `__str__()`, `__unicode__()`

Inherited from `object`

`__delattr__()`, `__getattr__()`, `__hash__()`, `__new__()`, `__reduce__()`, `__reduce_ex__()`, `__setattr__()`

8.4.2 Properties

Name	Description
<i>Inherited from <code>object</code></i>	
<code>__class__</code>	

8.5 Class `AbsoluteNumberThrottle`

`object` └─

`biblio.webquery.impl.ReprObj` └─

`biblio.webquery.querythrottle.BaseQueryThrottle` └─

`biblio.webquery.querythrottle.AbsoluteNumberThrottle`

Limit a query to a maximum number.

Many web-services have a per-day query limit (e.g. 500 per day for ISBNdb). It is difficult to implement this across multiple invocations of the query objects and Python interpreter, but this can serve as a crude implementation. By default, it raises an exception if the limit is reached.

8.5.1 Methods

`__init__(self, max, fail_action='RAISE')`

C'tor, allowing the maximum queries and failure behaviour to be set.

Parameters

max: The total number of queries allowed. (*type=int*)

fail_action: See `BaseQueryThrottle`.

Overrides: `object.__init__`

`within_limit(self, wquery)`

Have fewer queries been posted than the limit?

Note that if multiple queries simulatanoeusly test via this function, exceeding the limit is possible. **Parameters**

wquery: See `check_limit`

Overrides: `biblio.webquery.querythrottle.BaseQueryThrottle.within_limit`

`log_success(self, wquery)`

Successful queries will probably effect the success of future ones, so here is a place to log them. Overrides:

`biblio.webquery.querythrottle.BaseQueryThrottle.log_success` `exitit`(inherited documentation)

Inherited from `biblio.webquery.querythrottle.BaseQueryThrottle`(Section 8.2)

`check_limit()`

Inherited from `biblio.webquery.impl.ReprObj`(Section 5.2)

`__repr__()`, `__str__()`, `__unicode__()`

Inherited from `object`

`__delattr__()`, `__getattr__()`, `__hash__()`, `__new__()`, `__reduce__()`, `__reduce_ex__()`, `__setattr__()`

8.5.2 Properties

Name	Description
<i>Inherited from object</i>	
<code>__class__</code>	

8.6 Class `Max500Throttle`

object └─ `biblio.webquery.querythrottle.Max500Throttle`

Limit a query to 500 attempts at most.

This is a common limit, and so is provided as a convenience.

8.6.1 Methods

```
__init__(self)
x.__init__(...) initializes x; see x.__class__.__doc__ for signature
Overrides: object.__init__ extit(inherited documentation)
```

Inherited from object

```
__delattr__(), __getattr__(), __hash__(), __new__(), __reduce__(), __reduce_ex__(),
__repr__(), __setattr__(), __str__()
```

8.6.2 Properties

Name	Description
<i>Inherited from object</i>	
<code>__class__</code>	

9 Package *biblio.webquery.scripts*

Scripts that use *biblio.webquery*.

9.1 Modules

- **common**: Function shared between the scripts.
(Section 10, p. 28)
- **config**: Constants and definitions for scripts.
(Section 11, p. 29)
- **queryisbn**: Retrieve bibliographic information for a given ISBN.
(Section 12, p. 30)
- **renamebyisbn**: Rename files as by the ISBN buried in their original name.
(Section 13, p. 31)

10 Module `biblio.webquery.scripts.common`

Function shared between the scripts.

10.1 Functions

`add_shared_options(optparser)`

`check_shared_options(options, optparser)`

`construct_webquery(service, key)`

10.2 Variables

Name	Description
<code>script_version</code>	Value: <code>'0.4b'</code>

11 Module `biblio.webquery.scripts.config`

Constants and definitions for scripts. **Version:** 0.4b

11.1 Variables

Name	Description
WEBSERVICES	Value: [{'ctor': <class 'biblio.webquery.xisbn.XisbnQuery'>, 'id'...
DEFAULT_WEBSERVICE	Value: {'ctor': <class 'biblio.webquery.xisbn.XisbnQuery'>, 'id'...
WEBSERVICE_LOOKUP	Value: {'isbndb': {'ctor': <class 'biblio.webquery.isbndb.IsbnDb'...

12 Module `biblio.webquery.scripts.queryisbn`

Retrieve bibliographic information for a given ISBN.

12.1 Functions

<code>parse_args()</code>

<code>main()</code>

12.2 Variables

Name	Description
PRINT_FIELDS	Value: ['title', 'authors', 'publisher', 'year', 'lang']

13 Module *biblio.webquery.scripts.renamebyisbn*

Rename files as by the ISBN buried in their original name.

13.1 Functions

parse_args()

dir_base_ext_from_path(*fpath*)

Return a files base name and extension from it's path.

rename_file(*oldpath*, *newname*)

Rename a file, while keeping it in the same location.

extract_isbn_from_filename(*fname*)

generate_new_name(*bibrec*, *options*)

postprocess_name(*name*, *options*)

main()

13.2 Variables

Name	Description
ISBN10_PAT	Value: '(\d{9}[\d X])'
ISBN13_PAT	Value: '(\d{13})'
ISBN_PATS	Value: ['\\(ISBN([^\d X +])\\)', '^(\d{13})\$', '^(\d{13})[\\b _ ...]']
ISBN_RE	Value: [re.compile(r'(?i)\\(ISBN([^\d X +])\\)'), re.compile(r'(?i)^(...)]
DEF_NAME_FMT	Value: '%(auth)s%(year)s_%(short_title)s_(isbn%(isbn)s)'
DEF_STRIP_CHARS	Value: ':!,\`\'".?()'

continued on next page

Name	Description
DEF_BLANK_CHARS	Value: ''
STRIP_CHARS_RE	Value: <code>re.compile(r'[\':"!,\.\?\\(\)]')</code>
COLLAPSE_SPACE_RE	Value: <code>re.compile(r'\s+')</code>
CASE_CHOICES	Value: ['orig', 'upper', 'lower']
p	Value: <code>'\\D(\\d{9}[\\d X])\$'</code>

14 Module `biblio.webquery.utils`

Various utilities.

14.1 Functions

<code>normalize_isbn</code> (<i>isbn</i>)
Remove formatting from an ISBN, making it suitable for web-queries.

<code>parse_single_name</code> (<i>name_str</i>)
Clean up an individual name into a more consistent format.

parse_names(*name_str*)

Clean up a list of names into a more consistent format.

Xisbn data can be irregularly formatted, unpredictably including ancillary information. This function attempts to cleans up the author field into a list of consistent author names.

For example:

```
>>> n = parse_names ("Leonard Richardson and Sam Ruby.")
>>> print (n[0].family == 'Richardson')
True
>>> print (n[0].given == 'Leonard')
True
>>> print (not n[0].other)
True
>>> n = parse_names ("Stephen P. Schoenberger, Bali Pu-
lendran")
>>> print (n[0].family == 'Schoenberger')
True
>>> print (n[0].given == 'Stephen')
True
>>> print (n[0].other == 'P.')
True
>>> n = parse_names ("Madonna")
>>> print (not n[0].family)
True
>>> print (n[0].given == 'Madonna')
True
>>> print (not n[0].other)
True
```

Parameters

name_str: The “author” attribute from a Xisbn record in XML.
(*type=string*)

Return Value

A list of the authors in “reverse” format, e.g. “[’Smith, A. B.’, ’Jones, X. Y.’]”

parse_editing_info(*name_str*)

Detect whethers names are editors and returns

Returns: Whether editing information was recognised and the name with that editing information removed.

For example:

```
>>> parse_editing_info ("Leonard Richardson and Sam Ruby.")
(False, 'Leonard Richardson and Sam Ruby.')
>>> parse_editing_info ("Ann Thomson.")
(False, 'Ann Thomson.')
>>> parse_editing_info ("Stephen P. Schoenberger, Bali Pulendran, editors.")
(True, 'Stephen P. Schoenberger, Bali Pulendran')
>>> print parse_editing_info ("Madonna")
(False, 'Madonna')
```

parse_publisher(*pub_str*)

Parse a string of publisher information.

As with author names, publication details are often inconsistently set out, even in bibliographic data. This function attempts to parse out and normalise the details.

For example:

```
>>> parse_publisher ('New York: Asia Pub. House, c1979.')
('Asia Pub. House', 'New York', '1979')
>>> parse_publisher ('New York : LearningExpress, 1999.')
('LearningExpress', 'New York', '1999')
>>> parse_publisher ('HarperTorch')
('HarperTorch', '', '')
>>> parse_publisher ('Berkeley Heights, NJ: Enslow Publishers, c2000.')
('Enslow Publishers', 'Berkeley Heights, NJ', '2000')
```

Parameters

pub_str: text giving publisher details. (*type=string*)

Return Value

A tuple of strings, being (<publisher>, <city of publication>, <year of publication>). If no value is available, an empty string returned.

14.2 Variables

Name	Description
EDITOR_PATS	Value: [re.compile(r'(?iu)^edited by\s+'), re.compile(r'(?iu)\s*...
STRIP_PATS	Value: [re.compile(r'(?iu)^by\s+'), re.compile(r'(?iu)\s*;\s+wit...
AND_PAT	Value: re.compile(r'\s+and\s+')
COLLAPSE_SPACE_RE	Value: re.compile(r'\s+')
PUBLISHER_RES	Value: [re.compile(r'(?iu)^(?P<city>.*)\s*:\s*(?P<pub>.*)\s*,\s*...
p	Value: '^(?P<pub>.*)\.\.?\$',
x	Value: '\\s*;\s*.\$'

15 Module *biblio.webquery.worldcat*

Querying WorldCat for bibliographic information and normalising the results.

15.1 Functions

parse_authors(*auth_str*)

Clean up Worldcat author information into a more consistent format.

Worldcat data can be irregularly formatted, unpredictably including ancillary information. This function attempts to clean up the author field into a list of consistent author names.

For example:

```
>>> parse_authors ("Leonard Richardson and Sam Ruby.")
['Richardson, Leonard', 'Ruby, Sam']
>>> parse_authors ("Ann Thomson.")
['Thomson, Ann']
>>> parse_authors ("Stephen P. Schoenberger, Bali Pulendran, editors.")
['Schoenberger, Stephen P.', 'Pulendran, Bali']
>>> parse_authors ("Madonna")
['Madonna']
```

Parameters

auth_str: The “author” attribute from a Worldcat record in XML.
(*type=string*)

Return Value

A list of the authors in “reverse” format, e.g. “[’Smith, A. B.’, ’Jones, X. Y.’]”

parse_metadata(*mdata_xml*)

Retrieve fields from metadata and return and cleanup in a sensible form.

Parameters

mdata_xml: An Worldcat record in XML. (*type=string*)

Return Value

A dictionary with keys “year”, “title” and “authors” parsed from the Worldcat record. If a field is not present or parseable, neither is the key.

parse_title(*title*)

Clean up Worldcat title information into a more consistent format.

Although this currently does nothing, in the future it will normalise the titles, e.g. by stripping out subtitle and edition information.

15.2 Variables

Name	Description
AND_PAT	Value: <code>re.compile(r'\s+and\s+')</code>
STRIP_PATS	Value: <code>[re.compile(r'(?iu)^((edited)?by\s+)', re.compile(r'(?i...</code>
WORLDCAT_ROOTURL	Value: <code>'http://xisbn.worldcat.org/webservices/xid/isbn/'</code>
x	Value: <code>'\\([^\n])+\\'</code>

15.3 Class WorldcatQuery

object

biblio.webquery.impl.ReprObj

biblio.webquery.basewebquery.BaseWebquery

biblio.webquery.worldcat.WorldcatQuery

15.3.1 Methods

`__init__(self)`

C'tor. **Parameters**

root_url: The url to be used as the basis for all requests to this service. It should be the common “stem” that does not vary for any request.

timeout: How many seconds to wait for a response.

limits: A list of QueryThrottles to impose upon the use of this webservice.

Overrides: object.__init__

`query_mdata_by_isbn(self, isbn)`

Return publication data based on ISBN. **Parameters**

isbn: An ISBN-10 or ISBN-13. (*type=string*)

Return Value

Publication data in Worldcat XML format.

Inherited from `biblio.webquery.basewebquery.BaseWebquery` (Section 2.1)

`request()`

Inherited from `biblio.webquery.impl.ReprObj` (Section 5.2)

`__repr__()`, `__str__()`, `__unicode__()`

Inherited from `object`

`__delattr__()`, `__getattr__()`, `__hash__()`, `__new__()`, `__reduce__()`, `__reduce_ex__()`, `__setattr__()`

15.3.2 Properties

Name	Description
<i>Inherited from <code>object</code></i>	
<code>__class__</code>	

16 Module `biblio.webquery.xisbn`

Querying WorldCat xISBN service for bibliographic information.

16.1 Functions

`xisbn_py_to_bibrecord(pytxt)`

Translate the Python text returned by xISBN to a series of BibRecords.

Parameters

`pytxt`: An Xisbn record in Python. (*type=string*)

Return Value

A list of BibRecords.

16.2 Class `XisbnQuery`

object └

`biblio.webquery.impl.ReprObj` └

`biblio.webquery.basewebquery.BaseWebquery` └
`biblio.webquery.xisbn.XisbnQuery`

16.2.1 Methods

`__init__(self, timeout=5.0, limits=None)`

C'tor. **Parameters**

`root_url`: The url to be used as the basis for all requests to this service. It should be the common “stem” that does not vary for any request.

`timeout`: How many seconds to wait for a response.

`limits`: A list of QueryThrottles to impose upon the use of this webservice.

Overrides: `object.__init__`

```
query_service(self, isbn, method, format, fields=['*'])
```

A generalised query for xISBN.

This serves a general way of accessing all the methods available for xISBN. It also normalises the ISBN to a suitable form for submission. **Parameters**

isbn: A normalised ISBN-10 or -13. (*type=string*)

method: The request type to make of xISBN. (*type=string*)

format: The form for the response. (*type=string*)

fields: A list of the fields to include in the response.
(*type=iterable*)

Return Value

The response received from the service.

```
query_bibdata_by_isbn(self, isbn, format='bibrecord')
```

Return publication data based on ISBN. **Parameters**

isbn: An ISBN-10 or ISBN-13. (*type=string*)

Return Value

Publication data in Xisbn XML format.

```
query_editions_by_isbn(self, isbn, format='xml')
```

Return the editions associated with an ISBN. **Parameters**

isbn: An ISBN-10 or ISBN-13. (*type=string*)

format: See `query_service`. (*type=string*)

Return Value

Publication data in Xisbn XML format.

```
query_isbn(self, isbn, method, format='string')
```

A generalised method for ISBN queries that return ISBNs.

This allows functionality to be shared among the ISBN conversion and checking methods.

```
query_isbn10_to_13(self, isbn, format='string')
```

<code>query_isbn13_to_10(self, isbn, format='string')</code>
--

<code>query_fix_isbn_csum(self, isbn, format='string')</code>

<code>query_hyphenate_isbn(self, isbn, format='string')</code>
--

Inherited from biblio.webquery.basewebquery.BaseWebquery(Section 2.1)

`request()`

Inherited from biblio.webquery.impl.ReprObj(Section 5.2)

`__repr__()`, `__str__()`, `__unicode__()`

Inherited from object

`__delattr__()`, `__getattr__()`, `__hash__()`, `__new__()`, `__reduce__()`, `__reduce_ex__()`, `__setattr__()`

16.2.2 Properties

Name	Description
<i>Inherited from object</i>	
<code>__class__</code>	

17 Module `xml.etree.ElementTree`

17.1 Functions

`Comment(text=None)`

`Element(tag, attrib={}, **extra)`

`PI(target, text=None)`

`ProcessingInstruction(target, text=None)`

`SubElement(parent, tag, attrib={}, **extra)`

`XML(text)`

`dump(elem)`

`fromstring(text)`

`iselement(element)`

`parse(source, parser=None)`

`tostring(element, encoding=None)`

17.2 Variables

Name	Description
VERSION	Value: '1.2.6'

17.3 Class `ElementTree`

17.3.1 Methods

`__init__(self, element=None, file=None)`

`find(self, path)`

```
findall(self, path)
```

```
findtext(self, path, default=None)
```

```
getiterator(self, tag=None)
```

```
getroot(self)
```

```
parse(self, source, parser=None)
```

```
write(self, file, encoding='us-ascii')
```

17.4 Class QName

17.4.1 Methods

```
__cmp__(self, other)
```

```
__hash__(self)
```

```
__init__(self, text_or_uri, tag=None)
```

```
__str__(self)
```

17.5 Class TreeBuilder

17.5.1 Methods

```
__init__(self, element_factory=None)
```

```
close(self)
```

```
data(self, data)
```

```
end(self, tag)
```

```
start(self, tag, attrs)
```

17.6 Class XMLTreeBuilder

17.6.1 Methods

```
__init__(self, html=0, target=None)
```

```
close(self)
```

```
doctype(self, name, pubid, system)
```

```
feed(self, data)
```

17.7 Class XMLTreeBuilder

17.7.1 Methods

```
__init__(self, html=0, target=None)
```

```
close(self)
```

```
doctype(self, name, pubid, system)
```

```
feed(self, data)
```

17.8 Class iterparse

17.8.1 Methods

```
__init__(self, source, events=None)
```

```
__iter__(self)
```

```
next(self)
```

Index

- biblio (*package*)
 - biblio.webquery (*package*), 2
 - biblio.webquery.basewebquery (*module*), 3–5
 - biblio.webquery.bibrecord (*module*), 6–8
 - biblio.webquery.errors (*module*), 9–12
 - biblio.webquery.impl (*module*), 13–14
 - biblio.webquery.isbndb (*module*), 15–17
 - biblio.webquery.loc (*module*), 18–19
 - biblio.webquery.querythrottle (*module*), 20–26
 - biblio.webquery.scripts (*package*), 27
 - biblio.webquery.utils (*module*), 33–36
 - biblio.webquery.worldcat (*module*), 37–39
 - biblio.webquery.xisbn (*module*), 40–42
- xml (*package*)
 - xml.etree (*package*)
 - xml.etree.ElementTree (*module*), 43–45
 - xml.etree.ElementTree.Comment (*function*), 43
 - xml.etree.ElementTree.dump (*function*), 43
 - xml.etree.ElementTree.Element (*function*), 43
 - xml.etree.ElementTree.ElementTree (*class*), 43–44
 - xml.etree.ElementTree.ElementTree.__init__ (*function*), 43
 - xml.etree.ElementTree.ElementTree.find (*function*), 43
 - xml.etree.ElementTree.ElementTree.findall (*function*), 43
 - xml.etree.ElementTree.ElementTree.findtext (*function*), 44
 - xml.etree.ElementTree.ElementTree.getiterator (*function*), 44
 - xml.etree.ElementTree.ElementTree.getroot (*function*), 44
 - xml.etree.ElementTree.ElementTree.parse (*function*), 44
 - xml.etree.ElementTree.ElementTree.write (*function*), 44
 - xml.etree.ElementTree.iselement (*function*), 43
 - xml.etree.ElementTree.iterparse (*class*), 45
 - xml.etree.ElementTree.iterparse.__init__ (*function*), 45
 - xml.etree.ElementTree.iterparse.__iter__ (*function*), 45
 - xml.etree.ElementTree.iterparse.next (*function*), 45
 - xml.etree.ElementTree.parse (*function*), 43
 - xml.etree.ElementTree.ProcessingInstruction (*function*), 43
 - xml.etree.ElementTree.QName (*class*), 44
 - xml.etree.ElementTree.QName.__cmp__ (*function*), 44
 - xml.etree.ElementTree.QName.__hash__ (*function*), 44
 - xml.etree.ElementTree.QName.__init__ (*function*), 44
 - xml.etree.ElementTree.QName.__str__ (*function*), 44
 - xml.etree.ElementTree.SubElement (*function*), 43
 - xml.etree.ElementTree.tostring (*function*), 43
 - xml.etree.ElementTree.TreeBuilder (*class*), 44
 - xml.etree.ElementTree.TreeBuilder.__init__ (*function*), 44
 - xml.etree.ElementTree.TreeBuilder.close (*function*), 44
 - xml.etree.ElementTree.TreeBuilder.data (*function*), 44
 - xml.etree.ElementTree.TreeBuilder.end (*function*), 44
 - xml.etree.ElementTree.TreeBuilder.start (*function*), 44
 - xml.etree.ElementTree.XML (*function*), 43
 - xml.etree.ElementTree.XMLTreeBuilder (*class*),

44–45
xml.etree.ElementTree.XMLTreeBuilder.__init__
 (*function*), 45
xml.etree.ElementTree.XMLTreeBuilder.close
 (*function*), 45
xml.etree.ElementTree.XMLTreeBuilder.doctype
 (*function*), 45
xml.etree.ElementTree.XMLTreeBuilder.feed
 (*function*), 45