
pycddlib Documentation

Release 1.0.3

Matthias C. M. Troffaes

August 24, 2010

CONTENTS

1	Getting Started	3
1.1	Overview	3
1.2	Installation	3
2	Numerical Representations	5
3	Constants	9
4	Sets of Linear Inequalities and Generators	11
4.1	Methods and Attributes	11
4.2	Examples	12
5	Solving Linear Programs	17
5.1	Methods and Attributes	17
5.2	Examples	17
6	Working With Polyhedron Representations	21
6.1	Methods and Attributes	21
6.2	Examples	21
	Index	25

Release 1.0.3

Date August 24, 2010

GETTING STARTED

1.1 Overview

pycddlib is a Python wrapper for Komei Fukuda's cddlib.

cddlib is an implementation of the Double Description Method of Motzkin et al. for generating all vertices (i.e. extreme points) and extreme rays of a general convex polyhedron given by a system of linear inequalities.

The program also supports the reverse operation (i.e. convex hull computation). This means that one can move back and forth between an inequality representation and a generator (i.e. vertex and ray) representation of a polyhedron with cdd. Also, it can solve a linear programming problem, i.e. a problem of maximizing and minimizing a linear function over a polyhedron.

- Download: <http://pypi.python.org/pypi/pycddlib/#downloads>
- Documentation: <http://packages.python.org/pycddlib/>
- Development: <http://github.com/mcmtroffaes/pycddlib/>

1.2 Installation

1.2.1 Automatic Installer

The simplest way to install pycddlib, is to [download](#) an installer matching your version of Python, and run it.

1.2.2 Building From Source

MPIR

To compile pycddlib, you need [MPIR](#). On Linux, your distributions probably has a pre-built package for it. For example, on Fedora, install it by running:

```
yum install mpir-devel
```

On Windows, download the latest MPIR source tarball (decompress the `mpir-x.x.x.tar.bz2` file with [7-Zip](#)), and follow the instructions in `mpir-x.x.x\build.vc9\readme.txt`.¹ For pycddlib, you only need to build the `lib_mpir_gc` project. Once built, go to the `build.vc9\lib\win32\release` folder, and copy `mpir.h` to:

¹ When compiling extension modules, it is easiest to use same compiler that was used to compile Python. For Python 2.6, 2.7, 3.0, and 3.1, this is Microsoft Visual C/C++ 2008 (the [express](#) edition will do just fine).

```
C:\Program Files (x86)\Microsoft Visual Studio 9.0\VC\include
```

and `mpir.lib` and `mpir.pdb` to:

```
C:\Program Files (x86)\Microsoft Visual Studio 9.0\VC\lib
```

pycddlib

Once MPIR is installed, [download](#) and extract the source `.zip`. On Windows, start the MSVC command line, and run the setup script from within the extracted folder:

```
cd ....\pycddlib-x.x.x
C:\PythonXX\python.exe setup.py install
```

On Linux, start a terminal and run:

```
cd ....\pycddlib-x.x.x
python setup.py build
su -c 'python setup.py install'
```

1.2.3 Building From Git

To compile the *latest* code, clone the project with [Git](#) by running:

```
git clone --recursive git://github.com/mcmtroffaes/pycddlib
```

Then simply run the `build.sh` script: this will build the library, install it, generate the documentation, and run all the doctests. Note that, besides [MPIR](#), you also need [Cython](#) to compile the source, and [Sphinx](#) to generate the documentation.

NUMERICAL REPRESENTATIONS

`cdd.get_number_type_from_value(value)`

Determine number type from a value.

Returns 'fraction' if the value is `Fraction` or `str`, otherwise 'float'.

Return type `str`

`cdd.get_number_type_from_sequences(*data)`

Determine number type from sequences.

Returns 'fraction' if all elements are `Fraction` or `str`, otherwise 'float'.

Return type `str`

`class cdd.NumberTypeable(number_type='float')`

Base class for any class which admits different numerical representations.

Parameters

- **number_type** (`str`) – The number type ('float' or 'fraction').

```
>>> x = cdd.NumberTypeable()
>>> x.number_type
'float'
>>> x = cdd.NumberTypeable('float')
>>> x.number_type
'float'
>>> y = cdd.NumberTypeable('fraction')
>>> y.number_type
'fraction'
>>> # hyperreals are not supported :-)
>>> cdd.NumberTypeable('hyperreal')
Traceback (most recent call last):
...
ValueError: ...
```

`NumberTypeable.make_number(value)`

Convert value into a number.

Parameters

- **value** (`int`, `float`, or `str`) – The value to convert.

Returns The converted value.

Return type `NumberType`

```
>>> numbers = ['4', '2/3', '1.6', '-9/6', 1.12]
>>> nt = cdd.NumberTypeable('float')
>>> for number in numbers:
...     x = nt.make_number(number)
...     print(repr(x))
4.0
0.66666666666666663
1.6000000000000001
-1.5
1.1200000000000001
>>> nt = cdd.NumberTypeable('fraction')
>>> for number in numbers:
...     x = nt.make_number(number)
...     print(repr(x))
Fraction(4, 1)
Fraction(2, 3)
Fraction(8, 5)
Fraction(-3, 2)
Fraction(1261007895663739, 1125899906842624)
```

`NumberTypeable.number_str(value)`

Convert value into a string.

Parameters

- `value` (`NumberType`) – The value.

Returns A string for the value.

Return type `str`

```
>>> numbers = ['4', '2/3', '1.6', '-9/6', 1.12]
>>> nt = cdd.NumberTypeable('float')
>>> for number in numbers:
...     x = nt.make_number(number)
...     print(nt.number_str(x))
4.0
0.6666666666666667
1.6
-1.5
1.12
>>> nt = cdd.NumberTypeable('fraction')
>>> for number in numbers:
...     x = nt.make_number(number)
...     print(nt.number_str(x))
4
2/3
8/5
-3/2
1261007895663739/1125899906842624
```

`NumberTypeable.number_repr(value)`

Return representation string for value.

Parameters

- `value` (`NumberType`) – The value.

Returns A string for the value.

Return type `str`

```

>>> numbers = ['4', '2/3', '1.6', '-9/6', 1.12]
>>> nt = cdd.NumberTypeable('float')
>>> for number in numbers:
...     x = nt.make_number(number)
...     print(nt.number_repr(x))
4.0
0.66666666666666663
1.6000000000000001
-1.5
1.1200000000000001
>>> nt = cdd.NumberTypeable('fraction')
>>> for number in numbers:
...     x = nt.make_number(number)
...     print(nt.number_repr(x))
4
'2/3'
'8/5'
'-3/2'
'1261007895663739/1125899906842624'

```

`NumberTypeable.number_cmp(num1, num2=None)`

Compare values. Type checking may not be performed, for speed. If *num2* is not specified, then *num1* is compared against zero.

Parameters

- **num1** (`NumberType`) – First value.
- **num2** (`NumberType`) – Second value.

```

>>> a = cdd.NumberTypeable('float')
>>> a.number_cmp(0.0, 5.0)
-1
>>> a.number_cmp(5.0, 0.0)
1
>>> a.number_cmp(5.0, 5.0)
0
>>> a.number_cmp(1e-30)
0
>>> a = cdd.NumberTypeable('fraction')
>>> a.number_cmp(0, 1)
-1
>>> a.number_cmp(1, 0)
1
>>> a.number_cmp(0, 0)
0
>>> a.number_cmp(a.make_number(1e-30))
1

```

`NumberTypeable.number_type`

The number type as string.

```

>>> cdd.NumberTypeable().number_type
'float'
>>> cdd.NumberTypeable('float').number_type
'float'
>>> cdd.NumberTypeable('fraction').number_type
'fraction'

```

`NumberTypeable.NumberType`

The number type as class.

```
>>> cdd.NumberTypeable().NumberType
<type 'float'>
>>> cdd.NumberTypeable('float').NumberType
<type 'float'>
>>> cdd.NumberTypeable('fraction').NumberType
<class 'fractions.Fraction'>
```

CONSTANTS

class `cdd.LPObjType`
Type of objective for a linear program.

NONE
MAX
MIN

class `cdd.LPSolverType`
Type of solver for a linear program.

CRISS_CROSS
DUAL_SIMPLEX

class `cdd.LPStatusType`
Status of a linear program.

UNDECIDED
OPTIMAL
INCONSISTENT
DUAL_INCONSISTENT
STRUC_INCONSISTENT
STRUC_DUAL_INCONSISTENT
UNBOUNDED
DUAL_UNBOUNDED

class `cdd.RepType`
Type of representation. Use `INEQUALITY` for H-representation and `GENERATOR` for V-representation.

UNSPECIFIED
INEQUALITY
GENERATOR

SETS OF LINEAR INEQUALITIES AND GENERATORS

class `cdd.Matrix` (*rows*, *linear=False*, *number_type=None*)

A class for working with sets of linear constraints and extreme points.

Bases: `NumberTypeable`

Parameters

- **rows** (list of lists.) – The rows of the matrix. Each element can be an `int`, `float`, `Fraction`, or `str`.
- **linear** (`bool`) – Whether to add the rows to the `lin_set` or not.
- **number_type** (`str`) – The number type (`'float'` or `'fraction'`). If omitted, `get_number_type_from_sequences()` is used to determine the number type.

Warning: With the fraction number type, beware when using floats:

```
>>> print(cdd.Matrix([[1.12]], number_type='fraction')[0][0])
1261007895663739/1125899906842624
```

If the float represents a fraction, it is better to pass it as a string, so it gets automatically converted to its exact fraction representation:

```
>>> print(cdd.Matrix([[ '1.12' ]])[0][0])
28/25
```

Of course, for the float number type, both `1.12` and `'1.12'` will yield the same result, namely the `float` `1.12`.

4.1 Methods and Attributes

`Matrix.__getitem__` (*key*)

Return a row, or a slice of rows, of the matrix.

Parameters

- **key** (`int` or `slice`) – The row number, or slice of row numbers, to get.

Return type tuple of `NumberType`, or tuple of tuple of `NumberType`

`Matrix.canonicalize()`

Transform to canonical representation by recognizing all implicit linearities and all redundancies. These are returned as a pair of sets of row indices.

`Matrix.copy()`

Make a copy of the matrix and return that copy.

`Matrix.extend(rows, linear=False)`

Append rows to self (this corresponds to the `dd_MatrixAppendTo` function in `cdd`; to emulate the effect of `dd_MatrixAppend`, first call `copy` and then call `extend` on the copy).

The column size must be equal in the two input matrices. It raises a `ValueError` if the input rows are not appropriate.

Parameters

- **rows** (list of lists) – The rows to append.
- **linear** (bool) – Whether to add the rows to the `lin_set` or not.

`Matrix.row_size`

Number of rows.

`Matrix.col_size`

Number of columns.

`Matrix.lin_set`

A `frozenset` containing the rows of linearity (generators of linearity space for V-representation, and equations for H-representation).

`Matrix.rep_type`

Representation (see `RepType`).

`Matrix.obj_type`

Linear programming objective: maximize or minimize (see `LPObjType`).

`Matrix.obj_func`

A tuple containing the linear programming objective function.

4.2 Examples

Note that the following examples presume:

```
>>> import cdd
>>> from fractions import Fraction
```

4.2.1 Number Types

```
>>> cdd.Matrix([[1.5, 2]]).number_type
'float'
>>> cdd.Matrix([[1.5, 2]]).number_type
'float'
>>> cdd.Matrix([[Fraction(3, 2), 2]]).number_type
'float'
>>> cdd.Matrix([[1.5, 2]]).number_type
'fraction'
>>> cdd.Matrix([[Fraction(3, 2), Fraction(2, 1)]]).number_type
'fraction'
```


4.2.2 Fractions

Declaring matrices, and checking some attributes:

```
>>> mat1 = cdd.Matrix([[1', '2'], [3', '4']])
>>> mat1.NumberType
<class 'fractions.Fraction'>
>>> print(mat1)
begin
  2 2 rational
  1 2
  3 4
end
>>> mat1.row_size
2
>>> mat1.col_size
2
>>> print(mat1[0])
(1, 2)
>>> print(mat1[1])
(3, 4)
>>> print(mat1[2])
Traceback (most recent call last):
...
IndexError: row index out of range
>>> mat1.extend([[5,6]]) # keeps number type!
>>> mat1.row_size
3
>>> print(mat1)
begin
  3 2 rational
  1 2
  3 4
  5 6
end
>>> print(mat1[0])
(1, 2)
>>> print(mat1[1])
(3, 4)
>>> print(mat1[2])
(5, 6)
>>> mat1[1:3]
((3, 4), (5, 6))
>>> mat1[:-1]
((1, 2), (3, 4))
```

Canonicalizing:

```
>>> mat = cdd.Matrix([[2, 1, 2, 3], [0, 1, 2, 3], [3, 0, 1, 2], [0, -2, -4, -6]], number_type='fraction')
>>> mat.canonicalize()
(frozenset([1, 3]), frozenset([0]))
>>> print(mat)
linearity 1 1
begin
  2 4 rational
  0 1 2 3
  3 0 1 2
end
```



```
>>> mat1[1:3]
((3.0, 4.0), (5.0, 6.0))
>>> mat1[: -1]
((1.0, 2.0), (3.0, 4.0))
```

Canonicalizing:

```
>>> mat = cdd.Matrix([[2, 1, 2, 3], [0, 1, 2, 3], [3, 0, 1, 2], [0, -2, -4, -6]])
>>> mat.canonicalize()
(frozenset([1, 3]), frozenset([0]))
>>> print(mat)
linearity 1 1
begin
  2 4 real
  0 1 2 3
  3 0 1 2
end
```

Large number tests:

[illegible]

4.2.4 Other

Some regression tests:

```
>>> cdd.Matrix([[1], [1, 2]])
Traceback (most recent call last):
...
ValueError: rows have different lengths

>>> mat = cdd.Matrix([[1], [2]])
>>> mat.obj_func = (0, 0)
Traceback (most recent call last):
...
ValueError: objective function does not match matrix column size
```


SOLVING LINEAR PROGRAMS

class `cdd.LinProg` (*mat*)

A class for solving linear programs.

Bases: `NumberTypeable`

Parameters

- **mat** (`Matrix`) – The matrix to load the linear program from.

5.1 Methods and Attributes

`LinProg.solve` (*solver=cdd.LPSolverType.DUAL_SIMPLEX*)

Solve linear program.

Parameters

- **solver** (`int`) – The method of solution (see `LPSolverType`).

`LinProg.dual_solution`

A tuple containing the dual solution.

`LinProg.obj_type`

Whether we are minimizing or maximizing (see `LPObjType`).

`LinProg.obj_value`

The optimal value of the objective function.

`LinProg.primal_solution`

A tuple containing the primal solution.

`LinProg.solver`

The type of solver to use (see `LPSolverType`).

`LinProg.status`

The status of the linear program (see `LPStatusType`).

5.2 Examples

Note that the following examples presume:

```
>>> import cdd
```

5.2.1 Fractions

This is the testlp2.c example that comes with cddlib.

```
>>> mat = cdd.Matrix([['4/3', -2, -1], ['2/3', 0, -1], [0, 1, 0], [0, 0, 1]], number_type='fraction')
>>> mat.obj_type = cdd.LPObjType.MAX
>>> mat.obj_func = (0, 3, 4)
>>> print(mat)
begin
  4 3 rational
  4/3 -2 -1
  2/3 0 -1
  0 1 0
  0 0 1
end
maximize
  0 3 4
>>> print(mat.obj_func)
(0, 3, 4)
>>> lp = cdd.LinProg(mat)
>>> lp.solve()
>>> lp.status == cdd.LPStatusType.OPTIMAL
True
>>> print(lp.obj_value)
11/3
>>> print(" ".join("{0}".format(val) for val in lp.primal_solution))
1/3 2/3
>>> print(" ".join("{0}".format(val) for val in lp.dual_solution))
3/2 5/2
```

Another example.

```
>>> mat = cdd.Matrix([[1, -1, -1, -1], [-1, 1, 1, 1], [0, 1, 0, 0], [0, 0, 1, 0], [0, 0, 0, 1]], number_type='fraction')
>>> mat.obj_type = cdd.LPObjType.MIN
>>> mat.obj_func = (0, 1, 2, 3)
>>> lp = cdd.LinProg(mat)
>>> lp.solve()
>>> print(lp.obj_value)
1
>>> mat.obj_func = (0, -1, -2, -3)
>>> lp = cdd.LinProg(mat)
>>> lp.solve()
>>> print(lp.obj_value)
-3
>>> mat.obj_func = (0, '1.12', '1.2', '1.3')
>>> lp = cdd.LinProg(mat)
>>> lp.solve()
>>> print(lp.obj_value) # 28/25 is 1.12
28/25
>>> print(lp.primal_solution) # extreme point in simplex
(1, 0, 0)
```

5.2.2 Floats

This is the testlp2.c example that comes with cddlib.

```

>>> mat = cdd.Matrix([[4/3', -2, -1], [2/3', 0, -1], [0, 1, 0], [0, 0, 1]])
>>> mat.obj_type = cdd.LPObjType.MAX
>>> mat.obj_func = (0, 3, 4)
>>> print(mat)
begin
  4 3 real
  1.333333333E+00 -2 -1
  6.666666667E-01 0 -1
  0 1 0
  0 0 1
end
maximize
  0 3 4
>>> print(mat.obj_func)
(0.0, 3.0, 4.0)
>>> lp = cdd.LinProg(mat)
>>> lp.solve()
>>> lp.status == cdd.LPStatusType.OPTIMAL
True
>>> print(lp.obj_value)
3.66666...
>>> print(" ".join("{0}".format(val) for val in lp.primal_solution))
0.33333... 0.66666...
>>> print(" ".join("{0}".format(val) for val in lp.dual_solution))
1.5 2.5

```

Another example.

```

>>> mat = cdd.Matrix([[1, -1, -1, -1], [-1, 1, 1, 1], [0, 1, 0, 0], [0, 0, 1, 0], [0, 0, 0, 1]])
>>> mat.obj_type = cdd.LPObjType.MIN
>>> mat.obj_func = (0, 1, 2, 3)
>>> lp = cdd.LinProg(mat)
>>> lp.solve()
>>> print(lp.obj_value)
1.0
>>> mat.obj_func = (0, -1, -2, -3)
>>> lp = cdd.LinProg(mat)
>>> lp.solve()
>>> print(lp.obj_value)
-3.0
>>> mat.obj_func = (0, '1.12', '1.2', '1.3')
>>> lp = cdd.LinProg(mat)
>>> lp.solve()
>>> print(lp.obj_value) # 28/25 is 1.12
1.12

```


WORKING WITH POLYHEDRON REPRESENTATIONS

class `cdd.Polyhedron` (*mat*)

A class for converting between representations of a polyhedron.

Bases: `NumberTypeable`

Parameters

- **mat** (`Matrix`) – The matrix to load the polyhedron from.

6.1 Methods and Attributes

`Polyhedron.get_inequalities()`

Get all inequalities.

Returns H-representation.

Return type `Matrix`

`Polyhedron.get_generators()`

Get all generators.

Returns V-representation.

Return type `Matrix`

`Polyhedron.rep_type`

Representation (see `RepType`).

6.2 Examples

Note that the following examples presume:

```
>>> import cdd
```

6.2.1 Fractions

This is the `sampleh1.ine` example that comes with `cddlib`.

```
>>> mat = cdd.Matrix([[2,-1,-1,0],[0,1,0,0],[0,0,1,0]], number_type='fraction')
>>> mat.rep_type = cdd.RepType.INEQUALITY
>>> poly = cdd.Polyhedron(mat)
>>> print(poly)
begin
  3 4 rational
  2 -1 -1 0
  0 1 0 0
  0 0 1 0
end
>>> ext = poly.get_generators()
>>> print(ext)
V-representation
linearity 1 4
begin
  4 4 rational
  1 0 0 0
  1 2 0 0
  1 0 2 0
  0 0 0 1
end
>>> print(list(ext.lin_set)) # note: first row is 0, so fourth row is 3
[3]
```

This is the `testcdd2.c` example that comes with `cddlib`.

```
>>> mat = cdd.Matrix([[7,-3,-0],[7,0,-3],[1,1,0],[1,0,1]], number_type='fraction')
>>> mat.rep_type = cdd.RepType.INEQUALITY
>>> print(mat)
H-representation
begin
  4 3 rational
  7 -3 0
  7 0 -3
  1 1 0
  1 0 1
end
>>> print(cdd.Polyhedron(mat).get_generators())
V-representation
begin
  4 3 rational
  1 7/3 -1
  1 -1 -1
  1 -1 7/3
  1 7/3 7/3
end
>>> # add an equality and an inequality
>>> mat.extend([[7, 1, -3]], linear=True)
>>> mat.extend([[7, -3, 1]])
>>> print(mat)
H-representation
linearity 1 5
begin
  6 3 rational
  7 -3 0
  7 0 -3
  1 1 0
  1 0 1
  7 1 -3
```

```

    7 -3 1
end
>>> print(cdd.Polyhedron(mat).get_generators())
V-representation
begin
  2 3 rational
  1 -1 2
  1 0 7/3
end

```

6.2.2 Floats

This is the sample1.in example that comes with cddlib.

```

>>> mat = cdd.Matrix([[2,-1,-1,0],[0,1,0,0],[0,0,1,0]])
>>> mat.rep_type = cdd.RepType.INEQUALITY
>>> poly = cdd.Polyhedron(mat)
>>> print(poly)
begin
  3 4 real
  2 -1 -1 0
  0 1 0 0
  0 0 1 0
end
>>> ext = poly.get_generators()
>>> print(ext)
V-representation
linearity 1 4
begin
  4 4 real
  1 0 0 0
  1 2 0 0
  1 0 2 0
  0 0 0 1
end
>>> print(list(ext.lin_set)) # note: first row is 0, so fourth row is 3
[3]

```

This is the testcdd2.c example that comes with cddlib.

```

>>> mat = cdd.Matrix([[7,-3,-0],[7,0,-3],[1,1,0],[1,0,1]])
>>> mat.rep_type = cdd.RepType.INEQUALITY
>>> print(mat)
H-representation
begin
  4 3 real
  7 -3 0
  7 0 -3
  1 1 0
  1 0 1
end
>>> print(cdd.Polyhedron(mat).get_generators())
V-representation
begin
  4 3 real
  1 2.333333333E+00 -1
  1 -1 -1

```

```
1 -1 2.333333333E+00
1 2.333333333E+00 2.333333333E+00
end
>>> # add an equality and an inequality
>>> mat.extend([[7, 1, -3]], linear=True)
>>> mat.extend([[7, -3, 1]])
>>> print(mat)
H-representation
linearity 1 5
begin
  6 3 real
  7 -3 0
  7 0 -3
  1 1 0
  1 0 1
  7 1 -3
  7 -3 1
end
>>> print(cdd.Polyhedron(mat).get_generators())
V-representation
begin
  2 3 real
  1 -1 2
  1 0 2.333333333E+00
end
```

INDEX

Symbols

`__getitem__()` (cdd.Matrix method), 11

C

`canonicalize()` (cdd.Matrix method), 11

`col_size` (cdd.Matrix attribute), 12

`copy()` (cdd.Matrix method), 12

`CRISS_CROSS` (LPSolverType attribute), 9

D

`DUAL_INCONSISTENT` (LPStatusType attribute), 9

`DUAL_SIMPLEX` (LPSolverType attribute), 9

`dual_solution` (cdd.LinProg attribute), 17

`DUAL_UNBOUNDED` (LPStatusType attribute), 9

E

`extend()` (cdd.Matrix method), 12

G

`GENERATOR` (RepType attribute), 9

`get_generators()` (cdd.Polyhedron method), 21

`get_inequalities()` (cdd.Polyhedron method), 21

`get_number_type_from_sequences()` (in module cdd), 5

`get_number_type_from_value()` (in module cdd), 5

I

`INCONSISTENT` (LPStatusType attribute), 9

`INEQUALITY` (RepType attribute), 9

L

`lin_set` (cdd.Matrix attribute), 12

`LinProg` (class in cdd), 17

`LPObjType` (class in cdd), 9

`LPSolverType` (class in cdd), 9

`LPStatusType` (class in cdd), 9

M

`make_number()` (cdd.NumberTypeable method), 5

`Matrix` (class in cdd), 11

`MAX` (LPObjType attribute), 9

`MIN` (LPObjType attribute), 9

N

`NONE` (LPObjType attribute), 9

`number_cmp()` (cdd.NumberTypeable method), 7

`number_repr()` (cdd.NumberTypeable method), 6

`number_str()` (cdd.NumberTypeable method), 6

`number_type` (cdd.NumberTypeable attribute), 7

`NumberType` (cdd.NumberTypeable attribute), 7

`NumberTypeable` (class in cdd), 5

O

`obj_func` (cdd.Matrix attribute), 12

`obj_type` (cdd.LinProg attribute), 17

`obj_type` (cdd.Matrix attribute), 12

`obj_value` (cdd.LinProg attribute), 17

`OPTIMAL` (LPStatusType attribute), 9

P

`Polyhedron` (class in cdd), 21

`primal_solution` (cdd.LinProg attribute), 17

R

`rep_type` (cdd.Matrix attribute), 12

`rep_type` (cdd.Polyhedron attribute), 21

`RepType` (class in cdd), 9

`row_size` (cdd.Matrix attribute), 12

S

`solve()` (cdd.LinProg method), 17

`solver` (cdd.LinProg attribute), 17

`status` (cdd.LinProg attribute), 17

`STRUC_DUAL_INCONSISTENT` (LPStatusType attribute), 9

`STRUC_INCONSISTENT` (LPStatusType attribute), 9

U

`UNBOUNDED` (LPStatusType attribute), 9

`UNDECIDED` (LPStatusType attribute), 9

`UNSPECIFIED` (RepType attribute), 9